

According to regulation (EC)1907/2006

#### **SECTION 1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE COMPANY** 1.1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name:	SMARTMATERIALS RESIN STANDARD WHITE	
UFI:	EP00-1U0-1007-1AVA	
Product type:	Photopolymerizable resin.	

### 1.2 RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES DISAGREE

Recommended uses:	Resin for 3D printing. Additive manufacturing. Exclusive professional user use.
Uses advised against:	No information available.

#### **1.3 IDENTIFICATION OF THE COMPANY**

SMART MATERIALS 3D PRINTING SL Polígono Industrial El Retamar · C/ Tomillo 7 – Vial G 23680 Alcalá la Real (Jaén) SPAIN 2 +34 953 041 993 +34 953 113 527 info@smartmaterials3d.com www.smartmaterials3d.com

#### 1.4 EMERGENCY CONTACT

**Emergency phone:** 112

## **SECTION 2. HAZARDS IDENTIFICATION**

2.1 CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

#### CLP Regulation (EC) No 1272/2008

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008

Aquatic Chronic 4: Hazardous to the aquatic environment, long-term hazard, Category 4, H413 Skin Sens. 1B: Sensitisation, skin, Category 1B, H317

#### 2.2 LABEL ELEMENTS

Symbols / Pictograms:	Warning
Warning words:	Warning
Hazard statements:	Aquatic Chronic 4: H413 – May cause long lasting harmful effects to aquatic life. Skin Sens. 1B: h317 – May cause an allergic skin reaction.
Cautionary advice:	<ul> <li>P261: Avoid breathing dust/fume/gas/mist/vapours/spray</li> <li>P272: Contaminated wok clothing should not be allowed out of the workplace.</li> <li>P273: Avoid release to the environment.</li> <li>P280: Wear protective gloves/protective clothing/eye protection/face protection.</li> <li>P302+P352: IF ON SKIN: Wash with plenty of water.</li> <li>P333+P313: If skin irritation or rash occurs: Get medical advice/attention.</li> <li>P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.</li> </ul>
Supplementary information:	Contains Diphenyl (2,4,6-trimethylbenzoyl) phosphine oxide, pentaerythritol tetraacrylate. UFI: 9610-11YC-V006-0DCQ

www.smartmaterials3d.com 1



According to regulation (EC)1907/2006

2.3 OTHER HAZARDS:

Product fails to meet PBT/vPvB criteria

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

**3.1 SUBSTANCE** 

Non-applicable.

#### 3.2 CHEMICAL CHARACTERIZATION: MIXTURES

In accordance with Annex II of Regulation (EC) No 1907/2006, the product contains:

Chemical n	ame/Classification			Identification	%	
Esterification	products of 4,4' -isopropylidenediphenol, ethoxylated and 2-	0.16 1. 16 1.	CAS:	41637-38-1		
methylprop-2-enoic acid <sup>(1)</sup>		Self-classified	CE:	609-946-4		
Regulation	America Observice & UMAD		Index:	Non-applicable	85 - 100	
1272/2008	Aquatic Chronic 4: H413		REACH:	01-2119980659-17-XXXX		
			CAS:	4986-89-4	3 - 9	
Pentaerythrito	I tetraacrylate <sup>(1)</sup>	ATP CLP00	CE:	225-644-1		
Regulation	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Warning	$\langle \mathbf{I} \rangle$	Index:	607-122-00-9		
1272/2008	Eye imi. 2. H319, Skin imi. 2. H315, Skin Sens. 1. H317 - Warning	$\checkmark$	REACH:	Non-applicable		
Dinhonyl (2.4.)	6-trimetrhylbenzoyl) phosphine oxide (1)	Self-classified	CAS:	75980-60-8	2 - 2.5	
Jipnenyi (2,4,6	o-trimetrnyibenzoyi) phosphine oxide (4)	Self-classified	CE:	278-355-8		
Regulation	Aquatic Chronic 2: H411; Repr. 2: H361f; Skin Sens. 1B: H317 -	$\wedge$	Index:	015-203-00-X		
1272/2008	Warning		REACH:	01-2119972295-29-XXXX		
Ciclohexane <sup>(2)</sup>		ATP CLP00	CAS:	110-82-7	0.01 - 0.	
			CE:	203-806-2		
Regulation	egulation Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Asp. Tox. 1:		Index:	601-017-00-1		
1272/2008	H304; Flam. Liq.2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 -Danger	(!) (ð) (\$) (\$)	REACH:	01-2119463273-41-XXXX		
Toluene <sup>(2)</sup>		ATP CLP00	CAS:	108-88-3		
l oluelle (4)		ATP CLP00	CE:	203-625-9	0.01 - 0.1	
Regulation	Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315;		Index:	601-021-00-3	0.01-0	
272/2008	STOT RE2: H373; STOT SE 3: H336 - Danger	$\vee \vee \vee$	REACH:	01-2119471310-51-XXXX		
N-butyl acetat	a <sup>(2)</sup>		CAS:	123-86-4	<0.1	
N-Dulyi acelal		ATP CLP00	CE:	204-658-1		
Regulation	Flam. Lig. 3: H226 STOT SE 3: H336; EUH066 - Warning	(1) (3)	Index:	607-025-00-1		
1272/2008	riarn. Liq. 3: H226 STOT SE 3: H336; EUH066 - Warning		REACH:	01-2119485493-29-XXXX		
Phenol <sup>(2)</sup>		ATP CLP00	CAS:	108-95-2	<0.01	
		ATF CLEUU	CE:	203-632-7		
Regulation	Acute Tox. 3: H301+H311+H331; Muta. 2: H341; Skin Corr. 1B:		Index:	604-001-00-2	0.01	
272/2008	H314; STOT RE 2: H373 - Danger		REACH:	01-2119471329-32-XXXX		

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>(2)</sup> Substance with a Union workplace exposure limit

## **SECTION 4. FIRS AID MEASURES**

#### 4.1 DESCRIPTION OF FIRS AID MEASURES

By eye contact	: In case of irritation caused by the fumes, rinse immediately with plenty of water, also under the eyelids. If symptoms persist, contact your doctor.
By skin contact	: May produce an allergic reaction on the skin. In case of contact, it is recommended to clean the affected area with water by dragging and with neutral soap. In case of skin changes (itching, redness, rashes, blisters), go to a doctor with this Safety Data Sheet.
By inhalation	: It is a product not classified as dangerous by inhalation, however, in case of symptoms of poisoning it is recommended to remove the affected person from the place of exposure, supply them with clean air and keep them at rest. Seek medical attention if symptoms persist.
By ingestion	: Do not induce vomiting, if it occurs keep the head tilted forward to avoid aspiration. Keep the patient at rest. Rinse the mouth and throat, as there is a possibility that they have been affected on ingestion.

www.smartmaterials3d.com 2



According to regulation (EC)1907/2006

#### 4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, ACUTE AND DELAYED

Acute and delayed effects are listed in Sections 2 and 11.

#### 4.3 INDICATIONS FOR MEDICAL ATTENTION AND SPECIAL TREATMENTS THAT SHOULD BE GIVEN IMMEDIATELY

No hay information available

# SECTION 5. FIREFIGHTING MEASURES

### 5.1 EXTINGUISHING MEDIA

Suitable extinguishing media	: Non-flammable product under normal conditions of storage, handling and use, containing flammable substances. In case of ignition as a consequence of handling, storage or improper use, preferably use multipurpose powder extinguishers (ABC powder), in accordance with the Regulation of fire protection installations (R.D. 513/2017 and subsequent modifications).
Unsuitable extinguishing media	: It is recommended not to use full jet water as an extinguishing agent.

#### 5.2 SPECIAL HAZARDS ARISING FORM THE SUBSTANCE OR MIXTURE

Because of combustion or thermal decomposition, reaction by-products are generated that can be highly toxic and, consequently, can present a high risk to health.

#### **5.3 ADVICE FOR FIREFIGHTER**

Instructions	: No fighting instruction is required.
Special protective equipment for firefighters	: As in any fire, wear MSHA / NIOSH pressure-demand self-contained breathing apparatus (approved or equivalent) and all necessary protective equipment.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

For personnel who are not part of the emergency services	: Isolate leaks if it does not pose an additional risk to persons performing this function. Evacuate the area and keep unprotected people away. In the event of potential contact with the spilled product, the use of personal protection elements is mandatory (see SECTION 8). Avoid as a priority the formation of flammable vapor-air mixtures, either through ventilation or the use of an inerting agent. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all conductive surfaces on which static electricity can form, while the assembly is grounded.
For emergency personnel	: Wear with appropriate personal protective equipment (see SECTION 8).

#### **6.2 ENVIRONMENTAL PRECAUTIONS**

Avoid at all costs any type of spillage into the aquatic environment. Adequately contain the absorbed / collected product in hermetically sealable containers. Notify the competent authority in the event of exposure to the public or the environment.

### 6.3 METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING

#### It is recommended:

Absorb spillage with sand or inert absorbent and move to a safe place. Do not absorb in sawdust or other combustible absorbents. For any consideration regarding disposal, consult SECTION 13.



According to regulation (EC)1907/2006

## **SECTION 7. HANDLING AND STORAGE** 7.1 PRECAUTIONS FOR SAFE HANDLING

General precautions	: Comply with current legislation on the prevention of occupational hazards. Keep containers tightly closed. Control spills and residues, eliminating them with safe methods (SECTION 6). Avoid free spillage from container. Maintain order and cleanliness where dangerous products are handled.
Technical recommendations for the prevention of fires and explosions	: Avoid evaporation of the product as it contains flammable substances, which can form flammable vapor / air mixtures in the presence of ignition sources. Control ignition sources (mobile phones, sparks) and transfer at slow speeds to avoid the generation of electrostatic charges. Consult SECTION 10 on conditions and materials to avoid.
Technical recommendations to prevent ergonomic and toxicological hazards	: For exposure control consult SECTION 8. Do not eat, drink, or smoke in work areas; wash hands after each use and remove contaminated clothing and protective equipment before entering eating areas.
Technical recommendations to prevent environmental risks	: Due to the danger of this product for the environment, it is recommended to handle it within an area that has pollution control barriers in case of spillage, as well as to have absorbent material in the vicinity of it.

## 7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Requirements for the warehouse and containers	: Store in a dry place, protect from sunlight, store between 5ºC and 30ºC.
Rules for joint storage	: Not necessary.
Additional information on storage conditions	: Store in tightly closed containers in a cool, dry place.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION 8.1 CONTROL PARAMETERS

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occup	Occupational exposure limits		
Cyclohexane	IOELV (8h)	200 ppm	700 mg/m <sup>3</sup>	
CAS: 110-82-7 CE: 203-806-2	IOELV (STEL)	-	-	
Toluene	IOELV (8h)	50 ppm	192 mg/m <sup>3</sup>	
CAS: 108-88-3 CE: 203-625-9	IOELV (STEL)	100 ppm	384 mg/m <sup>3</sup>	
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m <sup>3</sup>	
CAS: 123-86-4 CE: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m <sup>3</sup>	
Phenol	IOELV (8h)	2 ppm	8 mg/m <sup>3</sup>	
CAS: 108-95-2 CE: 203-632-7	IOELV (STEL)	4 ppm	16 mg/m <sup>3</sup>	



According to regulation (EC)1907/2006

## DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Esterification products of 4,4' -	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
isopropylidenediphenol, ethoxylated and 2- methyplprop-2enoic acid	Dermal	Non-applicable	Non-applicable	2 mg/ Kg	Non-applicable
CAS: 41637-38-1 CE: 608-946-4	Inhalation	Non-applicable	Non-applicable	3,52 mg/ m <sup>3</sup>	Non-applicable
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 75980-60-8	Dermal	Non-applicable	Non-applicable	0,233 mg/ Kg	Non-applicable
CE: 278-355-8	Inhalation	Non-applicable	Non-applicable	0,822 mg/ m <sup>3</sup>	Non-applicable
Cyclohexane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 110-82-7	Dermal	Non-applicable	Non-applicable	2016 mg/ Kg	Non-applicable
CE: 203-806-2	Inhalation	1400 mg/ m <sup>3</sup>	1400 mg/ m <sup>3</sup>	700 mg/ m <sup>3</sup>	700 mg/ m <sup>3</sup>
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-88-33	Dermal	Non-applicable	Non-applicable	384 mg/ Kg	Non-applicable
CE: 203-625-9	Inhalation	384 mg/ m <sup>3</sup>	384 mg/ m <sup>3</sup>	192 mg/ m <sup>3</sup>	192 mg/ m <sup>3</sup>
N-butyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 123-86-4	Dermal	11 mg/kg	Non-applicable	11 mg/kg	Non-applicable
CE: 204-658-1	Inhalation	600 mg/ m <sup>3</sup>	600 mg/ m <sup>3</sup>	300 mg/ m <sup>3</sup>	300 mg/ m <sup>3</sup>
Phenol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	1,23 mg/ Kg	Non-applicable
CE: 203-632-7	Inhalation	Non-applicable	16 mg/ m <sup>3</sup>	8 mg/ m <sup>3</sup>	Non-applicable

## DNEL (General population):

		Short	exposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Esterification products of 4,4' - isopropylidenediphenol, ethoxylated and 2-	Oral	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
methyplprop-2enoic acid	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable
CAS: 41637-38-1 CE: 608-946-4	Inhalation	Non-applicable	Non-applicable	0,87 mg/ m³	Non-applicable
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide CAS: 75980-60-8	Oral	Non-applicable	Non-applicable	0,0833 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,0833 mg/kg	Non-applicable
CE: 278-355-8	Inhalation	Non-applicable	Non-applicable	0,145 mg/m <sup>3</sup>	Non-applicable
Cyclohexane CAS: 110-82-7	Oral	Non-applicable	Non-applicable	59,4 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	1186 mg/kg	Non-applicable
CE: 203-806-2	Inhalation	412 mg/m <sup>3</sup>	412 mg/ m <sup>3</sup>	206 mg/m <sup>3</sup>	206 mg/m <sup>3</sup>
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable
CAS: 108-88-33	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable
CE: 203-625-9	Inhalation	226 mg/m³	226 mg/m³	56,5 mg/m³	56,5 mg/m³
N-butyl acetate	Oral	2 mg/kg	Non-applicable	2 mg/kg	Non-applicable
CAS: 123-86-4	Dermal	6 mg/kg	Non-applicable	6 mg/kg	Non-applicable
CE: 204-658-1	Inhalation	300 mg/m <sup>3</sup>	300 mg/m³	35,7 mg/m <sup>3</sup>	35,7 mg/m³
Phenol	Oral	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
CAS: 108-95-2	Dermal	Non-applicable	Non-applicable	0,4 mg/kg	Non-applicable
CE: 203-632-7	Inhalation	Non-applicable	Non-applicable	1,32 mg/m <sup>3</sup>	Non-applicable



According to regulation (EC)1907/2006

### PNEC:

Identification				
	STP	Non-applicable	Water	0.0014 mg/L
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	Soil	0,0222 mg/Kg	Marine water	0,00014 mg/L
CAS: 75980-60-8 CE: 278-355-8	Intermittent	0,014 mg/L	Sediment (Water)	0.115 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.0115 mg/kg
cyclohexane AS: 110-82-7	STP	3.24 mg/L	Water	0.207 mg/L
	Soil	3.38 mg/kg	Marine water	0.207 mg/L
CAS: 110-82-7 CE: 203-806-2	Intermittent	0.207 mg/L	Sediment (Water)	16.68 mg/Kg
	Oral	Non-applicable	Sediment (Marine water)	6.68 mg/Kg
	STP	13.61 mg/L	Water	0.68 mg/L
Toluene	Soil	2.89 mg/kg	Marine water	0.68 mg/L
CAS: 108-88-33 CE: 203-625-9	Intermittent	0.68 mg/L	Sediment (Water)	16.39 mg/kg
AS: 108-88-33	Oral	Non-applicable	Sediment (Marine water)	16.39 mg/kg
	STP	35.6 mg/L	Water	0.18 mg/L
N-butyl acetate	Soil	0.09 mg/kg	Marine water	0.018 mg/L
CAS: 123-86-4 CE: 204-658-1	Intermittent	0.36 mg/L	Sediment (Water)	0.981 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.098 mg/kg
	STP	2.1 mg/L	Water	0.008 mg/L
Phenol	Soil	0.136 mg/kg	Marine water	0.001 mg/L
CAS: 108-95-2 CE: 203-632-7	Intermittent	0.031 mg/L	Sediment (Water)	0.091 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0.009 mg/kg

#### 8.2 EXPOSURE CONTROL

A.- Individual protection measures, such as personal protective equipment

As a preventive measure, the use of basic personal protective equipment is recommended, with the corresponding CE marking in accordance with R.D. 1407/1992 and subsequent modifications. For more information on personal protective equipment (storage, use, cleaning, maintenance, protection class ...) consult the information leaflet provided by the PPE manufacturer. The indications contained in this point refer to the pure product. The protection measures for the diluted product may vary depending on its degree of dilution, use, application method, etc. To determine the obligation to install emergency showers and / or eyewashes in warehouses, the regulations regarding the storage of chemical products applicable in each case will be considered. For more information see sections 7.1 and 7.2.

All the information included here is a recommendation, and it is necessary to specify it by the occupational risk prevention services as it is not aware of the additional prevention measures that the company may have or if they have been included in the relevant risk assessment.

Respiratory prot	PPE	Labelling	CEN Standard	Observations
Mandatory respiratory tract protection	Self-filtering mask for gases and vapours (Filter type: FFP2)		EN 405:2002+A1:2010	Replace when the odor or taste of the contaminant is detected inside the mask or face adapter. When the pollutant does not have good warning properties, the use o insulating equipment is recommended.



According to regulation (EC)1907/2006



Self-filtering mask for gases and vapors (Filter type: A)



EN 405:2002+A1:2010 Replace when the odor or taste of the contaminant is detected inside the mask or face adapter. When the pollutant does not have good warning properties, the use of insulating equipment is recommended.

## C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Observations
Mandatory hand protection	Protective gloves against minor risks (Material: Nitrile)	CATI	EN 420:2004 A1:2010 EN ISO 374-1:2016 A1:2018	Replace the gloves at any sign of deterioration. For prolonged periods of exposure to the product for professional / industrial users, the use of CE III gloves is recommended.

Since the product is a mixture of different materials, the resistance of the glove material cannot be calculated in advance with complete reliability and therefore must be checked before application.

#### D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Observations
Mandatory face protection	Goggles against splashes and / or projections		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Its use is recommended in case of risk of splashing.

#### E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Observations
	Work clothing	CATI	EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994	Replace before any indication of deterioration. For prolonged periods of exposure to the product for professional / industrial users CE III is recommended.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any indication of deterioration. For prolonged periods of exposure to the product for professional / industrial users CE III is recommended,

#### E.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

#### **Environmental exposure controls:**

Under Community environmental protection legislation, it is recommended to avoid spilling both the product and its packaging into the environment. For additional information see section 7.1.D



According to regulation (EC)1907/2006

#### Volatile organic compounds:

In application to R.D. 117/2003 and subsequent modifications (Directive 2010/75 / EU), this product has the following characteristics:

V.O.C (Supply):	0,21 % weight
V.O.C DENSITY at 20 °C:	2,42 kg/m <sup>3</sup> (2,04 g/L)
Average carbon number:	6,43
Average molecular weight:	92,08 g/mol

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES 9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: Liquid
Appearance	: Viscous
Colour	: White
Odour	: Resin
Density	:1.129 g/cm <sup>3</sup>
Kinematic viscosity at 40ºC	: <20,5 mm²/s
рН	: 6 – 8 (al 100%)
Flash point	: Non-flammable (>60°C)
Autoignition temperature	: 260 °C

#### 9.2 OTHER INFORMATION

Non available

## SECTION 10. STABILITY AND REACTIVITY 10.1 REACTIVITY

## None are expected under normal use conditions.

#### **10.2 CHEMYCAL STABILITY**

Stable under recommended storage conditions.

#### **10.3 POSSIBILITY OF HAZARDOUS REACTIONS**

None are expected under normal use conditions.

**10.4 CONDITIONS TO AVOID** 

Caution against overheating. Caution against sunlight. Prolonged exposure will cause product degradation.

#### **10.5 INCOMPATIBLE MATERIALS**

### Avoid strong acids. Avoid alkalis or strong bases.

### **10.6 HAZARDOUS DECOMPOSITION PRODUCTS**

See SECTION 5.2

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### **11.1 INFORMATION ON TOXICOLOGICAL EFFECTS**

There are no experimental data on the product itself regarding toxicological properties.



According to regulation (EC)1907/2006

Version 1.0/EN Revision Date: 20/10/2021

#### Dangerous effects for health:

In case of repetitive or prolonged exposure or at concentrations higher than those established by the occupational exposure limits, adverse health effects may occur depending on the route of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for ingestion. For more information see SECTION 3.
  - Corrosivity / Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for this effect. For more information see SECTION 3.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous by Inhalation. For more information see SECTION 3.
  - Corrosivity / Irritability: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for this effect. For more information see SECTION 3.
- C- Contact with skin and eyes (acute effect):
  - Contact with the skin: Based on the available data, the classification criteria are not met, however, it contains substances classified as dangerous for contact with the skin. For more information see SECTION 3.
  - Eye contact: Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see SECTION 3.
- D- CMR effects (carcinogenicity, mutagenicity y toxicity for reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects described. For more information see SECTION 3. IARC: Toluene (3); Phenol (3); Carbon black (2B).
  - Mutagenicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous with mutagenic effects. For more information see SECTION 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for this effect. For more information see SECTION 3.
- E- Sensitizing effect:
  - Respiratory: Based on the available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitizing effects above the limits set forth in point 3.2 of Regulation (EC) 2015/830. For more information see sections 2, 3 and 15.
     Dermal Brelenged context with the skip conclused to RDE acdium from allergic context dermatities.
    - Dermal: Prolonged contact with the skin can lead to PPE sodium from allergic contact dermatitis.
- F- Specific Target Organ Toxicity (STOT)-single exposure:

Based on available data, the classification criteria are not met, however, it does contain substances classified as dangerous by Inhalation. For more information see SECTION 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT) -repeated exposure: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous by repetitive exposure. For more information see SECTION 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see SECTION 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, however, it does contain substances classified as dangerous for this effect. For more information see SECTION 3.



According to regulation (EC)1907/2006

## Specific toxicological information of the substances:

Identification	Acute t	oxicity	Genus
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	DL50 oral	5500 mg/kg	Rat
CAS: 75980-60-8	DL50 Dermal	Non-applicable	
CE: 278-355-8	DL50 Inhalation	Non-applicable	
Cyclohexane	DL50 oral	5100 mg/Kg	Rat
CAS: 110-82-7	DL50 Dermal	Non-applicable	
CE: 203-806-2	DL50 Inhalation	Non-applicable	
Toluene	DL50 oral	5580 mg/kg	Rat
Toluene CAS: 108-88-33	DL50 Dermal	12124 mg/kg	Rat
CE: 203-625-9	DL50 Inhalation	28,1 mg/L (4 h)	Rat
N-hutyl acetate	DL50 oral	12789 mg/kg	Rat
CAS: 123-86-4	DL50 Dermal	14112 mg/kg	Rabbit
CE: 204-658-1	DL50 Inhalation	23,4 mg/L (4 h)	Rat
Phenol	DL50 oral	100 mg/kg	Rat
E: 203-806-2 oluene CAS: 108-88-33 CE: 203-625-9 I-butyl acetate CAS: 123-86-4 CE: 204-658-1 Phenol CAS: 108-95-2	DL50 Dermal	630 mg/kg	Rabbit
CE: 203-632-7	DL50 Inhalation	Non-applicable	

## **SECTION 12. ECOLOGICAL INFORMATION**

#### **12.1 TOXICITY**

Identification	A	cute toxicity	Species	Genus
Diphenyl(2,4,6-trimethylbenzoyl) phosphine oxide	LC50	>1 – 10 (96 h)		Fish
CAS: 75980-60-8	EC50	>1 – 10 (48 h)		Crustacean
CE: 278-355-8	EC50	>1 – 10 (72 h)		Algae
Cyclohexane	LC50	>1 – 10 (96 h)		Fish
S: 110-82-7	EC50	>1 – 10 (48 h)		Crustacean
CE: 203-806-2	EC50	>1 – 10 (72 h)		Algae
Toluene CAS: 108-88-33 CE: 202-625-0	LC50	13 mg/L (96 h)	Carassius auratus	Fish
	EC50	11.5 mg/L (48 h)	Daphnia magna 💦	Crustacean
CE: 203-625-9	EC50	125 mg/L (48 h)	Scenedesmus subspicatus	Algae
N-butyl acetate	LC50	62 mg/L (96 h)	Leuciscus idus	Fish
CAS: 123-86-4	EC50	73 mg/L (24 h)	Daphnia magna	Crustacean
CE: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
Phenol	LC50	14 mg/L (96 h)	Leuciscus idus	Fish
CAS: 108-95-2	EC50	12 mg/L (24 h)	Daphnia magna	Crustacean
CE: 203-632-7	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae

#### 12.2 PERSISTENCE AND DEGRADABILITY

GE: 203-032-7	EC50	370 mg/L (96 h)	Chlorella vulgaris	Algae	
12.2 PERSISTENCE AND DEGRADABILITY		sr	nar	tn	1 8
Identification	Degr	adability	Biodegi	radability	
Cyclohexane	BOD5	Non-applicable	Concentration	100 mg/L	
CAS: 110-82-7	COD	Non-applicable	Period	28 días	
CE: 203-806-2	BOD5/COD	Non-applicable	% Biodegradable	0 %	
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L	
CAS: 108-88-33	COD	Non-applicable	Period	14 días	
CE: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %	
N-butyl acetate CAS: 123-86-4	BOD5	Non-applicable	Concentration	Non-applicable	
	COD	Non-applicable	Period	5 days	
CE: 204-658-1	BOD5/COD	Non-applicable	% Biodegradable	84 %	

www.smartmaterials3d.com 10



## SAFETY DATA SHEET SMART MATERIALS RESIN STANDARD WHITE

#### Version 1.0/EN Revision Date: 20/10/2021

According to regulation (EC)1907/2006

Phenol	BOD5	1,68 g O2/g	Concentration	100 mg/L
CAS: 108-95-2	COD	2,33 g O2/g	Period	14 días
CE: 203-632-7	BOD5/COD	0,72	% Biodegradable	85 %

## 12.3 BIOACCUMULATIVE POTENTIAL

	Identification	Bioad	cumulation potential
Cyclohexane		BCF	66
CAS: 110-82-7 CE: 203-806-2		Pow Log	3,44
		Potential	Moderate
Toluene CAS: 108-88-33 CE: 203-625-9		BCF	13
		Pow Log	2,73
		Potential	Low
N-butyl acetate CAS: 123-86-4 CE: 204-658-1		BCF	4
		Pow Log	1,48
		Potential	Low
Phenol CAS: 108-95-2 CE: 203-632-7		BCF	17
		Pow Log	1,48
		Potential	Low

#### 12.4 MOBILITY IN SOIL

Identification	Absorption	Absorption/Desorption		Volatility	
Cyclohexane CAS: 110-82-7 CE: 203-806-2	Кос	Non-applicable	Henry	100 mg/L	
	Conclusion	Non-applicable	Dry soil	28 días	
	Surface tension	Non-applicable	Moist soil	0 %	
Toluene CAS: 108-88-33 CE: 203-625-9	Кос	2,5 g O2/g	Henry	100 mg/L	
	Conclusion	Non-applicable	Dry soil	14 días	
	Surface tension	Non-applicable	Moist soil	100 %	
N-butyl acetate CAS: 123-86-4 CE: 204-658-1	Кос	Non-applicable	Henry	Non-applicable	
	Conclusion	Non-applicable	Dry soil	Non-applicable	
	Surface tension	2,78E-2 N/m (25°C)	Moist soil	Non-applicable	
Phenol CAS: 108-95-2 CE: 203-632-7	Кос	1,68 g O2/g	Henry	100 mg/L	
	Conclusion	2,33 g O2/g	Dry soil	14 días	
	Surface tension	0,72	Moist soil	85 %	

#### 12.5 RESULTS OF PBT AND vPvB ASSESSMENT

Non-applicable

#### 12.6 OTHERS ADVERSE EFFECTS

No information available

# SECTION 13. DISPOSAL CONSIDERATIONS

## 13.1 WASTE TREATMENT METHODS

Code	Description	Waste class (Regulation (EU) nº 1357/2014)
20 01 27*	Paint, inks, adhesives, and resins containing hazardous substances	Dangerous

## Type of waste (Regulation (UE) nº 1357/2014):

HP14 Ecotoxic

smart



#### Waste management (disposal and evaluation):

Consult the authorized waste manager for recovery and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98 / EC, Law 22/2011). According to codes 15 01 (2014/955 / EU), if the container has been in direct contact with the product, it will be managed in the same way as the product itself, otherwise it will be managed as non-hazardous waste. Dumping into water courses is discouraged. See section 6.2.

#### Legislative provisions related to waste management:

In accordance with Annex II of Regulation (EC) No. 1907/2006 (REACH), the community or state provisions related to waste management are included.

Community legislation: Directive 2008/98 / EC, 2014/955 / EU, Regulation (EU) No. 1357/2014 National legislation: Law 22/2011, Royal Decree 180/2015, Law 11/1997

#### **SECTION 14. TRANSPORT INFORMATION**

ADR	: No regulated
RID	: No regulated
ΙΑΤΑ	: No regulated
IMDG	: No regulated

#### **SECTION 15. REGULATORY INFORMATION**

# 15.1 SAFETY, HEALTH AND ENVIRONMENTAL STANDARDS / LEGISLATION SPECIFIC TO THE SUBSTANCE OF THE

#### MIXTURE

Candidate substances for authorization in Regulation (EC) 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH (authorization list) and expiration date: non-applicable Regulation (EC) 1005/2009, on substances that deplete the ozone layer: non-applicable Active substances which have been included in Article 95 of Regulation (EU) No. 528/2012: Non-applicable REGULATION (EU) No 649/2012, relative to the export and import of dangerous chemical products: non-applicable

#### Seveso III:

Non-applicable

# Restrictions on the marketing and use of certain dangerous substances and mixtures (Annex XVII of the REACH regulation, etc. ...):

Shall not be used in:

- Decorative items intended to produce lighting or colour effects obtained through different phases, for example, ambient lamps and ashtrays,
- Fun and joke articles,
- Games for one or more participants or any item that is going to be used as such, even with a decorative character.

Occupational exposure to respirable crystalline silica must be controlled in accordance with Directive (EU) 2019/130.

#### Specific provisions regarding the protection of people or the environment:

It is recommended to use the information collected in this safety data sheet as input data in a risk assessment of local circumstances to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:



According to regulation (EC)1907/2006

Regulation (EC) No. 1272/2008 of the European Parliament and of the Council, of December 16, 2008, on classification, labelling and packaging of substances and mixtures, and which modifies and repeals Directives 67/548 / EEC and 1999 / 45 / EC and Regulation (EC) No. 1907/2006 and all its subsequent amendments are amended.

#### 15.2 CHEMICAL SAFETY ASSESSMENT

The supplier has not carried out evaluation of chemical safety.

#### **SECTION 16. OTHER INFORMATION**

#### Legislation applicable to safety data sheets:

This safety data sheet has been developed in accordance with ANNEX II-Guide for the preparation of Safety Data Sheets

of Regulation (CE) No. 1907/2006 (Regulation (EU) No. 2015/830)

#### Modifications with respect to the previous safety data sheet that affect risk management measures:

Non-applicable

#### Texts of the legislative phrases contemplated in SECTION 2:

H413: May be harmful to aquatic life with long lasting effects. H317: May cause an allergic skin reaction.

#### Texts of the legislative phrases contemplated in SECTION 3:

The phrases indicated do not refer to the product itself, they are for information only and refer to the individual

components that appear in SECTION 3

#### Regulation nº1272/2008 (CLP):

Acute Tox. 3: H301 + H311 + H331 - Toxic if swallowed, in contact with skin or Inhalation. Aquatic Acute 1: H400 - Very toxic to aquatic organisms. Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Aquatic Chronic 4: H413 - May be harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Irrit. 2: H319 - Causes serious eye irritation. Flam. Liq. 2: H225 - Highly flammable liquid and vapor. Mutates. 2: H341 - Suspected of causing genetic defects. Repr. 2: H361d - Suspected of damaging the fetus. Repr. 2: H361f - Suspected of damaging fertility. Skin Corr. 1B: H314 - Causes severe skin burns and eye damage. Skin Irrit. 2: H315 - Causes Dermal irritation. Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1B: H317 - May cause an allergic skin reaction. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure. STOT SE 3: H336 - May cause drowsiness or dizziness.

#### **Classification procedure:**

Aquatic Chronic 4: Calculation method Skin Sens. 1B: Calculation method

#### Advice regarding training:



According to regulation (EC)1907/2006

Minimum training in occupational risk prevention is recommended for the personnel who are going to handle this product, to facilitate the understanding and interpretation of this safety data sheet, as well as the labeling of the product.

#### Main bibliographic sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### Abbreviations and acronyms:

ADR: European Agreement on the International Transport of Dangerous Goods by Road IMDG: International Maritime Dangerous Goods Code IATA: International Air Transport Association ICAO: International Civil Aviation Organization COD: Chemical Oxygen Demand BOD5: Biological Oxygen Demand at 5 days BCF: Bioconcentration Factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective Concentration 50 Log POW: Logarithm Octanol Water Partition Coefficient Koc: Organic Carbon Partition Coefficient SDS: Safety Data Sheet UFI: unique formula identifier IARC: International Agency for Research on Cancer

The data that can be extracted from this safety data sheet is based on the current state of our knowledge, this information should be treated as a guide for transport, safe storage, and handling. The information provided does not constitute any guarantee of the product's qualities. Furthermore, it is the user's responsibility to handle the product in accordance with local regulations and standards.

The information provided in this security sheet does not generate any contractual legal relationship.